

Technospray 3

High performance, medium duty, low foam formulation designed for use in single or multi-stage aqueous degreasing machinery.

It's excellent inter stage and storage anticorrosion properties make it an ideal system for all substrates. It also gives excellent performance results on sensitive materials such as cast steel, aluminium, copper and brass.

Built into the formulation is a water-softening package that assists in the maintenance of outstanding cleanliness results in areas where water hardness of up to 400ppm is encountered. Due to these properties Technospray 3 is ideally suited for all wash systems.

The low ph in concentrate (10.4) and at working solutions of 1 - 2% (9.6) create a safer alternative to corrosive products without the loss of performance.

Optimum v/v strengths are between 1 – 2%; working solution life consistently achieves a range of 8 -12 weeks at wash temperatures between 55 -70°C. When combined with its low disposal costs Technospray 3 can significantly contribute to low operational costs.

A simple test kit allows the operator to determine on a daily basis that the Technospray 3 wash solution is within recommended parameters thus insuring that best possible results are achieved where quality assurance specifications are critical.

Typical applications include automotive component manufactures, diesel generator manufactures, construction and heavy plant manufactures (JCB), general and precision engineering companies.

Packaging options available, 25 litre containers, 200 litre barrels and 1000 litre IBC (intermediate bulk containers)

For information on applications or to discuss a potential trial contact us at info@sonikem.co.uk